



IAG Billet Floor Mat Bracket for 2005-09 Legacy

Part# IAG-BDY-1201

Tools Required: 14mm socket, ratchet, torque wrench, small pick

Contents: *Billet IAG Bracket w/ stud and bolt attached x1*
O-ring x3

Thank you for choosing IAG Performance. The billet floor mat bracket is designed to replace the factory plastic clip that often rips through the carpet. This not only ruins your carpet but allows your floor mats to slide forward and bunch up near the pedals. Please follow the instructions below for an easy installation.

Removal:

1. Pull up on the factory floor mat and remove it from the vehicle. Using a flat head screw driver or pliers carefully pry and remove the factory clip from the carpet. If your carpet is already torn, you can simply pull it out.

2. Remove the front seat bolt using the 14mm socket and ratchet.



1.



2.



Install:

3. Place the IAG bracket in the vehicle as shown. Hand tighten the bolt



3.

4. Place the floor mat back in the vehicle and slide the hole over the stud as shown.



4.

5. Press the o-ring into the groove on the top of the stud.



5.



6. Torque the front seat bolt to 39lb/ft



6.

****Tech Tip****

We supply 2 extra O-rings in case you remove the original and misplace it. We recommend keeping them in the car inside the small plastic bag they came in.

